


| Pozicija | Kol. | Opis |
|----------|------|---|
| | 1 | <p>ALPHA2 25-60 180</p>  <p>Št. proizvoda: 97993201</p> <ul style="list-style-type: none"> • AUTOADAPT function automatically finds the best setpoint and thus reduces the energy consumption and setup time. • Insulating shells are supplied with pumps to minimise ENERGY heat loss in heating and cooling systems. • A display shows the actual power consumption in Watt or actual flow rate in m³/h for control purposes. • The best energy efficiency index (EEI) in the market provides the highest energy savings during a year. • Stainless-steel pump housings are available if the application demand corrosion resistance or for drinking water, DHW applications. • Complies with the German regulation for energy saving in buildings and building systems, Energieeinsparverordnung – EnEV §14(3). • Automatic night setback function that further reduces the energy consumption if the boiler provides this feature. • Simple selection among three constant-pressure curves, three proportional-pressure curves or three fixed speeds with only one button. Quick and simple setup. • ALPHA plug. Easy, quick and safe electrical connection. • ALPHA2 is suitable for cold-water systems, drinking water approval. High application flexibility. • Electro-coated pump housing. • No external motor protection is required. Reduced installation time and costs. • New improved start. Secure start under tough conditions. • New advanced. Dry-running protection. Protects the pump at initial start-up and daily operation if there is no water in the pump. • Manual summer mode. Saves energy during the summertime –consumption <0,8W and ensures safe start at the next heating season. <p>Teko ina: rpana teko ina: Voda Razpon temperature teko ine: 2 .. 110 °C Liquid temperature during operation: 60 °C Specifi na teža: 983.2 kg/m³</p> <p>Tehni ni podatki: TF razred: 110 Odobritive na napisni tablici: VDE,GS,CE,EAC</p> <p>Materiali: Ohišje rpalke: Siva litina EN-GJL-150 ASTM A48-150B Teka : PES 30%GF</p> <p>Montaža: Razpon temperature okolice: 0 .. 40 °C</p> |

| Pozicija | Kol. | Opis |
|----------|------|--|
| | | Maks. delovni tlak: 10 bar Cevni priključek: G 1 1/2 Tlačna stopnja: PN 10 Vgradna dolžina: 180 mm |
| | | Električni podatki: Vhodna moč - P1: 3 .. 34 W Omrežna frekvenca: 50 Hz Nominalna napetost: 1 x 230 V Maksimalna poraba toka: 0.04 .. 0.32 A Razred zaščit (IEC 34-5): X4D Izolacijski razred (IEC 85): F |
| | | Drugo: Energy (EEI): 0.17 Neto teža: 2.01 kg Bruto teža: 2.13 kg Transportni volumen: 0.004 m ³ Danish: VVS NO 38 0471.061 Swedish: RSK NO 5731810 Finnish LVI No.: LVI NO 4615238 Norwegian NRF no.: NRF NO 9042045 |